

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

---

5-12-1978

## Test 1276: White Field Boss 2-155 DSL 18-Speed

Tractor Museum

University of Nebraska-Lincoln, [TractorMuseumArchives@unl.edu](mailto:TractorMuseumArchives@unl.edu)

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

---

Museum, Tractor, "Test 1276: White Field Boss 2-155 DSL 18-Speed" (1978). *Nebraska Tractor Tests*. 1595.

<https://digitalcommons.unl.edu/tractormuseumlit/1595>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# NEBRASKA TRACTOR TEST 1276 — WHITE FIELD BOSS 2-155 DSL ALSO WHITE FARM EQUIPMENT 2-155 DIESEL 18 SPEED

## POWER TAKE-OFF PERFORMANCE

Power Hp (kW)	Crank shaft speed rpm	Fuel Consumption			Temperature °F (°C)			Barometer inch Hg (kPa)	
		gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Cooling medium	Air wet bulb	Air dry bulb		
MAXIMUM POWER AND FUEL CONSUMPTION									
Rated Engine Speed—Two Hours (PTO Speed—1015 rpm)									
157.73 (117.62)	2200	10.434 (39.495)	0.458 (0.278)	15.12 (2.978)	189 (87.4)	56 (13.2)	75 (23.8)	28.997 (97.917)	
Standard Power Take-Off Speed (1000 rpm)—One Hour									
162.37 (121.08)	2167	10.555 (39.955)	0.450 (0.274)	15.38 (3.030)	190 (87.9)	56 (13.1)	75 (24.0)	29.015 (97.979)	
VARYING POWER AND FUEL CONSUMPTION—Two Hours—									
138.09 (102.97)	2264	9.656 (36.552)	0.484 (0.294)	14.30 (2.817)	186 (85.6)	56 (13.3)	76 (24.2)	..... .....	
0.00 (0.00)	2397	3.308 (12.523)	..... .....	..... .....	175 (79.4)	56 (13.1)	75 (23.9)	..... .....	
71.49 (53.31)	2348	6.434 (24.357)	0.623 (0.379)	11.11 (2.189)	178 (81.4)	56 (13.3)	76 (24.2)	..... .....	
158.53 (118.22)	2199	10.436 (39.506)	0.455 (0.277)	15.19 (2.992)	189 (87.2)	56 (13.3)	76 (24.4)	..... .....	
36.29 (27.06)	2376	4.887 (18.498)	0.932 (0.567)	7.43 (1.463)	175 (79.4)	55 (12.8)	74 (23.6)	..... .....	
105.83 (78.92)	2315	8.121 (30.742)	0.531 (0.323)	13.03 (2.567)	184 (84.2)	56 (13.3)	76 (24.7)	..... .....	
Av Av	85.04 (63.41)	2317 (27.030)	7.140 (0.353)	0.581 (0.353)	11.91 (2.346)	181 (82.9)	56 (13.2)	76 (24.2)	29.017 (97.985)

## DRAWBAR PERFORMANCE

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption			Temp. °F (°C)			Barom. inch Hg (kPa)
					gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Cool- ing med	Air wet bulb	Air dry bulb	
Maximum Available Power—Two Hours 10th (3-O) Gear											
131.33 (97.93)	9145 (40.68)	5.39 (8.67)	2200	5.56	10.352 (39.186)	0.545 (0.332)	12.69 (2.499)	188 (86.4)	58 (14.4)	71 (21.7)	28.790 (97.220)
75% of Pull at Maximum Power—Ten Hours 10th (3-O) Gear											
106.18 (79.18)	6969 (31.00)	5.71 (9.19)	2295	3.95	9.210 (34.864)	0.600 (0.365)	11.53 (2.271)	184 (84.2)	57 (13.9)	66 (18.8)	28.800 (97.402)
50% of Pull at Maximum Power—Two Hours 10th (3-O) Gear											
73.30 (54.66)	4645 (20.66)	5.92 (9.52)	2343	2.58	7.353 (27.834)	0.694 (0.422)	9.97 (1.964)	178 (81.1)	58 (14.2)	64 (17.8)	28.850 (97.422)
50% of Pull at Reduced Engine Speed—Two Hours 14th (5-D) Gear											
73.62 (54.90)	4661 (20.73)	5.92 (9.53)	1433	2.50	5.221 (19.764)	0.491 (0.298)	14.10 (2.778)	179 (81.7)	60 (15.3)	69 (20.3)	28.895 (97.574)

## MAXIMUM POWER IN SELECTED GEARS

121.17 (90.36)	14512 (64.55)	3.13 (5.04)	2218	14.95	5th (2-D) Gear		183 (83.9)	55 (12.8)	60 (15.6)	28.850 (97.422)
123.74 (92.27)	13799 (61.38)	3.36 (5.41)	2200	14.70	6th (3-U) Gear		187 (86.1)	63 (17.2)	76 (24.4)	28.730 (97.017)
130.78 (97.52)	12410 (55.20)	3.95 (6.36)	2198	9.64	7th (2-O) Gear		189 (86.9)	63 (17.2)	76 (24.4)	28.740 (97.051)
135.29 (100.89)	11616 (51.67)	4.37 (7.03)	2198	8.04	8th (3-D) Gear		190 (87.5)	62 (16.7)	76 (24.4)	28.750 (97.084)
135.63 (101.14)	10597 (47.14)	4.80 (7.72)	2199	6.83	9th (4-U) Gear		189 (86.9)	61 (16.1)	75 (23.9)	28.760 (97.118)
133.59 (99.62)	9302 (41.38)	5.39 (8.67)	2200	5.52	10th (3-O) Gear		188 (86.4)	59 (15.0)	72 (22.2)	28.780 (97.186)
138.70 (103.43)	8843 (39.33)	5.88 (9.47)	2200	5.28	11th (4-D) Gear		189 (87.2)	63 (17.2)	76 (24.4)	28.740 (97.051)
135.88 (101.33)	7132 (31.72)	7.14 (11.50)	2200	4.01	12th (4-O) Gear		189 (86.9)	63 (17.2)	76 (24.4)	28.740 (97.051)
137.35 (102.43)	6914 (30.76)	7.45 (11.99)	2200	3.77	13th (5-U) Gear		187 (86.1)	63 (17.2)	76 (24.4)	28.730 (97.017)
139.68 (104.16)	5795 (25.78)	9.04 (14.55)	2200	3.12	14th (5-D) Gear		187 (86.1)	63 (17.2)	76 (24.4)	28.730 (97.017)

Department of Agricultural Engineering

Dates of Test: May 12 to May 19, 1978

Manufacturer: WHITE FARM EQUIPMENT  
CO., 2625 Butterfield Road, Oak Brook, Illinois  
60521

**FUEL, OIL AND TIME** Fuel No. 2 diesel  
Cetane No. 50.4 (rating taken from oil company's  
typical inspection data) **Specific gravity converted**  
**to 60°/60° (15°/15°)** 0.8310 **Fuel weight** 6.919 lbs/  
gal (0.829 kg/l) **Oil SAE 30 API service classifi-**  
**cation** SB/SE - CA/CD **To motor** 3.643 gal  
(13.789 l) **Drained from motor** 3.225 gal  
(12.207 l) **Transmission and final drive lubricant**  
Universal tractor hydraulic and transmission fluid  
**Total time engine was operated** 35.0 hours

**ENGINE:** Make White Diesel **Type** 6 cylinder  
vertical with turbocharger **Serial No.** 4005651  
**Crankshaft** lengthwise **Rated rpm** 2200 **Bore and**  
**stroke** 4.56" x 4.87" (115.8 mm x 123.7 mm) **Com-**  
**pression ratio** 17.0 to 1 **Displacement** 478 cu in  
(7834 ml) **Cranking system** 12 volt **Lubrication**  
pressure **Air Cleaner** primary and secondary  
paper elements with aspirator **Oil Filter** two full  
flow paper spin-on cartridges **Oil cooler** engine  
coolant heat exchanger for crankcase oil, radiator  
for hydraulic and transmission oil **Fuel filter** two  
paper elements **Muffler** vertical **Cooling medium**  
**temperature control** thermostat

**CHASSIS:** **Type** Standard with duals **Serial**  
**No.** 278741-414 **Tread width** rear 63" (1600 mm)  
to 126" (3200 mm) front 60" (1524 mm) to 84" (2134  
mm) **Wheel base** 113" (2870 mm) **Center of gravity**  
(without operator or ballast, with minimum tread,  
with fuel tank filled and tractor serviced for opera-  
tion) Horizontal distance forward from center-line  
of rear wheels 31.3" (794 mm) Vertical distance  
above roadway 41.6" (1057 mm) Horizontal dis-  
tance from center of rear wheel tread 0" (0 mm) to  
the right/left **Hydraulic control system** direct en-  
gine drive **Transmission** selective gear fixed ratio  
with partial (3) range operator controlled power  
shift **Advertised speeds** mph (km/h) first 2.2 (3.5)  
second 2.6 (4.2) third 2.8 (4.5) fourth 3.1 (5.0) fifth  
3.4 (5.5) sixth 3.7 (5.9) seventh 4.1 (6.6) eighth 4.4  
(7.1) ninth 4.8 (7.7) tenth 5.3 (8.5) eleventh 5.8 (9.3)  
twelfth 7.0 (11.3) thirteenth 7.2 (11.6) fourteenth  
8.7 (14.0) fifteenth 10.4 (16.7) sixteenth 12.3 (19.8)  
seventeenth 14.8 (23.8) eighteenth 17.8 (28.6) re-  
verse 2.5 (4.0), 3.0 (4.8), 3.6 (5.8), 4.3 (6.9), 5.2  
(8.4), 6.2 (10.0) **Clutch** single dry disc operated by  
foot pedal **Brakes** single wet disc hydraulically  
power actuated by two foot pedals which can be  
locked together **Steering** hydrostatic **Turning**  
**radius** (on concrete surface with brake applied)  
right 146" (3.71 m) left 146" (3.71 m) (on concrete  
surface without brake) right 165" (4.19 m) left 165"  
(4.19 m) **Turning space diameter** (on concrete sur-  
face with brake applied) right 298" (7.58 m) left  
298" (7.58 m) (on concrete surface without brake)  
right 336" (8.55 m) left 336" (8.55 m) **Power take-**  
**off** 1000 rpm at 2167 engine rpm

# LUGGING ABILITY IN 10th (3-O) Gear

Crankshaft Speed rpm	2200	1978	1752	1543	1305	1097
Pull—lbs (kN)	9302 (41.38)	11314 (50.33)	12316 (54.78)	12377 (55.05)	11059 (49.19)	9197 (40.91)
Increase in Pull %	0	22	32	33	19	-1
Power—Hp (kW)	133.59 (99.62)	143.22 (106.80)	135.51 (101.05)	119.97 (89.46)	92.32 (68.85)	65.85 (49.11)
Speed—Mph (km/h)	5.39 (8.67)	4.75 (7.64)	4.13 (6.64)	3.63 (5.85)	3.13 (5.04)	2.69 (4.32)
Slip %	5.52	7.44	9.06	9.06	7.44	5.60

# TRACTOR SOUND LEVEL WITH CAB dB(A)

Maximum Available Power—Two Hours	80.5
75% of Pull at Maximum Power—Ten Hours	79.5
50% of Pull at Maximum Power—Two Hours	80.0
50% of Pull at Reduced Engine Speed—Two Hours	79.5
Bystander in 18th (6-O) gear	87.5

# TIRES, BALLAST AND WEIGHT

<b>Rear Tires</b>	—No., size, ply & psi (kPa)
Ballast	—Liquid (each)
	—Cast Iron (each)
<b>Front Tires</b>	—No., size, ply & psi (kPa)
Ballast	—Liquid (each)
	—Cast Iron (each)

# Tested Without Ballast

Four 20.8-38; 8; 12 (80)
None
None
Two 14L-16; 1; 6; 28 (190)
None
None

# Height of Drawbar

21.0 in (535 mm)

# Static Weight with Operator—Rear

12520 lb (5679 kg)

# —Front

4130 lb (1873 kg)

# —Total

16650 lb (7552 kg)

**REPAIRS and ADJUSTMENTS:** No repairs or adjustments

**REMARKS:** All test results were determined from observed data obtained in accordance with SAE and ASAE test code or official Nebraska test procedure. Temperature at injection pump was 166°F (74.5°C). Ten gears were chosen between 15% slip and 10 mph (16.1 km/h).

We, the undersigned, certify that this is a true and correct report of official Tractor Test 1276.

LOUIS I. LEVITICUS

Engineer-in-Charge

G. W. STEINBRUEGGE, Chairman

W. E. SPLINTER

K. VON BARGEN

Board of Tractor Test Engineers



White Field Boss 2-155 DSL